

LASER LEVELS & SENSORS

CATALOG 2024



THE STORY OF KAPRO



ABOUT US

For over 30 years, we have dedicated ourselves to the development and production of the best layout and measuring tools in the market. Our spirit levels, laser levels and layout and marking tools are produced with the customer in mind and are manufactured to the highest possible quality and standards.

Through our state of the art facilities in Israel, China and the United States, we have built a global network of partners that cater the needs of professionals around the world.

INNOVATION & DESIGN

Kapro's R&D team has revolutionized the layout & measuring tool design, introducing a variety of ground-breaking inventions to the market:

The Plumb Site® Dual-view™- the only level feature in the market providing a frontal view of the plumb vial, eliminating parallax error as well as neck and back strain due to vertical plumb jobs.

The OptiVision® Red Vial - a new standard in vial visibility, achieved by creating a clear color outline around the spirit level's bubble. The clearest, most visible vial on the market today.

Laser positioning legs – with anti-slip grips and multiple angle options, our patented strong folding legs simplify angle mounting and height adjustment of lasers.

Prolaser® levels – offer a complete line of powerful lasers, that when combined with variable combination sets, offer the customer a staggering array of choices.

Specialty levels – unique levels that cater the specific needs of professionals in various trades such as drywall installation, plumbing and electrical work.

QUALITY

Kapro is dedicated to excellence in every aspect: production, distribution, sales and marketing.

We solely use the highest quality materials and components, from the strongest yet lightest steel and aluminium spirit levels to the most advanced, reliable modules in laser levels.

Kapro is the only level manufacturer in the world to carry the prestigious VPA mark of quality and all our manufacturing facilities are compliant with ISO Standards 9001, 14001 and SA8000. All Kapro lasers and electronic products carry FDA and CE certification, and comply with RoHS, WEEE and REACH regulations.

In addition, Kapro adheres to strict calibration and testing standards for all products, ensuring the highest level of accuracy in the market.

SERVICE & VALUE

The Kapro team strives to supply value to our customers through excellent products and the highest level of service. Our dedicated customer service team is constantly listening and responding to customers, ensuring their needs are met in a professional and timely manner.



CONTENT

ABOUT US	3
ROTARY LASERS	6
LINE LASERS	8
DOT LASERS	23
DIY LASERS	24
OPTICAL LEVELS	25
LASER SETS	26
SENSORS	28
LASER ACCESSORIES	32

8991G/8991

PROLASER® ELECTROTA®



QUALITY ASSURANCE

IP65
WATER & DUST
RESISTANT


2 YEAR
LIMITED
WARRANTY

TECHNICAL DATA

- Accuracy: ± 0.1 mm/m (± 0.0001 in/in)
- Self-leveling: $\pm 5^\circ$
- Self-leveling type: Electronic
- Manual leveling of up to $\pm 5^\circ$ in both X and Y planes for slopes and gradients
- Laser range with detector: 50 m (165 ft)
- Laser range with detector: 300 m (980 ft)
- Protective shock absorbing cover
- Durable handles
- 5 customizable rotation speeds: 0 (Stationary Point), 60, 120, 300, 600 rpm
- 6 scan modes create visible laser lines for diverse applications
- Visual & audible "Out of Leveling Range" warning
- 5/8" tripod thread for flat & 90° mounting

KIT INCLUDES

- Remote control
- Laser detector
- Beamfinder™ glasses
- Laser target
- Rechargeable batteries
- Battery charger
- 2 X battery brackets for regular & rechargeable batteries
- Shockproof protective case



884G

PROLASER® 4D XTRA



QUALITY ASSURANCE

IP54
WATER & DUST
RESISTANT

3 YEAR
LIMITED
WARRANTY

TECHNICAL DATA

- Accuracy: ± 0.15 mm/m (± 0.00015 in/in)
- Self-leveling: $\pm 4^\circ$
- Self-leveling type: Electronic
- Laser range without detector: 30 m (100 ft)
- Laser range with detector: 70 m (230 ft)
- Shock resistant rubber over molded cover
- Visual & audible "Out of Leveling Range" warning
- Manual mode for angular layout / marking
- Pulse mode
- 1/4" tripod thread


KIT INCLUDES

- 2 X rechargeable Li-Ion batteries
- Charger
- Multi-purpose magnetic mount
- Beamfinder™ glasses
- Elevating platform
- Laser target
- Carrying case



864G

PROLASER® 4D ALL LINES



QUALITY ASSURANCE

IP65
WATER & DUST
RESISTANT


3 YEAR
LIMITED
WARRANTY

TECHNICAL DATA

- Accuracy: ± 0.2 mm/m (± 0.0002 in/in)
- Self-leveling: $\pm 3^\circ$
- Self-leveling type: Pendulum
- Laser range without detector: 30 m (100 ft)
- Laser range with detector: 60 m (200 ft)
- Shock resistant rubber over molded cover
- Visual & audible "Out of Leveling Range" warning
- Manual mode for angular layout / marking
- Pulse mode
- 1/4" tripod thread
- Type C port for charging


KIT INCLUDES

- 2 X rechargeable Li-Ion batteries
- Charger
- Multi-purpose magnetic mount
- Beamfinder™ glasses
- Elevating platform
- Laser target
- Carrying case



8831G

PROLASER® 3D ALL LINES



QUALITY ASSURANCE




TECHNICAL DATA

- Accuracy: ± 0.2 mm/m (± 0.0002 in/in)
- Self-leveling: $\pm 3^\circ$
- Self-leveling type: Pendulum
- Laser range without detector: 30 m (100 ft)
- Laser range with detector: 60 m (200 ft)
- Shock resistant rubber over molded cover
- Visual & audible "Out Of Leveling Range" warning
- Manual mode for angular layout / marking
- Pulse mode
- 1/4" tripod thread
- Type C port for charging


KIT INCLUDES

- 2 X rechargeable lithium batteries
- Type-C USB charger
- Multi-purpose magnetic mount
- Beamfinder™ glasses
- Laser Target
- Carrying case



8832G

PROLASER® 3D ALL LINES



QUALITY ASSURANCE




TECHNICAL DATA

- Accuracy: ± 0.2 mm/m (± 0.0002 in/in)
- Self-leveling: $\pm 3^\circ$
- Self-leveling type: Pendulum
- Laser range without detector: 30 m (100 ft)
- Laser range with detector: 60 m (200 ft)
- Shock resistant rubber over molded cover
- Visual & audible "Out Of Leveling Range" warning
- Manual mode for angular layout / marking
- Pulse mode
- Bottom and top 1/4" thread
- Type C port for charging

KIT INCLUDES

- 2 X rechargeable lithium batteries
- Type-C USB charger
- Multi-purpose magnetic mount
- Beamfinder™ glasses
- Elevating platform
- Laser target
- Carrying case




883G/883

PROLASER® 3D ALL LINES



LASER BEAM LAYOUT



QUALITY ASSURANCE

IP65
WATER & DUST
RESISTANT

3 YEAR
LIMITED
WARRANTY

TECHNICAL DATA

- Accuracy: ± 0.2 mm/m (± 0.0002 in/in)
- Self-leveling: $\pm 2.5^\circ$
- Self-leveling type: Pendulum
- Green laser range:
 - Without detector: 30 m (100 ft)
 - With detector: 70 m (230 ft)
- Red laser range:
 - Without detector: 30 m (100 ft)
 - With detector: 60 m (230 ft)
- Shock resistant rubber over molded cover
- Visual "Out of Leveling Range" warning
- Manual mode for angular layout / marking
- Pulse mode
- 1/4" and 5/8" tripod threads

OPTIONAL

- 883GB with softbag (no wall mount & ceiling clamp)

KIT INCLUDES


- Multi-purpose magnetic mount
- 2 x rechargeable lithium batteries
- AA batteries holder
- Beamfinder™ glasses
- Laser target
- Carrying case

863G/863

CROSSLIGHT™ 3D



LASER BEAM LAYOUT



QUALITY ASSURANCE

IP54
WATER & DUST
RESISTANT

2 YEAR
LIMITED
WARRANTY

TECHNICAL DATA

- Accuracy: ± 0.3 mm/m (± 0.0003 in/in)
- Self-leveling: $\pm 4^\circ$
- Self-leveling type: Pendulum
- Green laser range:
 - Without detector: 30 m (100 ft)
 - With detector: 60 m (200 ft)
- Red laser range:
 - Without detector: 20 m (65 ft)
 - With detector: 50 m (165 ft)
- Protective shock absorbing cover
- Visual & audible "Out of Leveling Range" warning
- Manual mode for angular layout / marking
- Pulse mode
- 1/4" tripod thread


KIT INCLUDES

- Rechargeable lithium battery
- Battery charger
- Wall mount
- Top mount adapter
- Carrying case



875G/875

PROLASER® ALL LINES



— QUALITY ASSURANCE —

IP54
WATER & DUST
RESISTANT

3 YEAR
LIMITED
WARRANTY

— TECHNICAL DATA —

- Accuracy: ± 0.2 mm/m (± 0.0002 in/in)
- Self-leveling: $\pm 2.5^\circ$
- Self leveling type: Pendulum
- Green laser range:
 - Without detector: 30 m (100 ft)
 - With detector: 60 m (200 ft)
- Red laser range:
 - Without detector: 30 m (100 ft)
 - With detector: 50 m (165 ft)
- Shock resistant rubber over molded cover
- Adjustable support legs
- Manual mode for angular layout / marking
- Pulse mode
- 360° rotation with fine adjustment knob
- Top surface bubble level
- 5/8" Tripod thread

— OPTIONAL —

- 875S/ 875GS PROLASER® Layout Set with tripod (886-28) & Carrying case
- 875 HYBRID PROLASER® ALL-LINES Red & green beams version

— KIT INCLUDES —

- 2 x rechargeable lithium battery
- Beamfinder™ Glasses
- Laser target
- Micro USB charging cable
- Soft carrying case

962G/962

PROLASER® MULTIBEAM ORBITAL LASER



— QUALITY ASSURANCE —

IP65
WATER & DUST
RESISTANT

2 YEAR
LIMITED
WARRANTY

— TECHNICAL DATA —

- Accuracy: ± 0.3 mm/m (± 0.0003 in/in)
- Self-leveling: $\pm 3^\circ$
- Self leveling type: Pendulum
- Green laser range:
 - Without detector: 30 m (100 ft)
 - With detector: 60 m (200 ft)
- Red laser range:
 - Without detector: 30 m (100 ft)
 - With detector: 50 m (165 ft)
- Shock resistant rubber over molded cover
- Manual mode for angular layout / marking
- Pulse mode
- 1/4" and 5/8" tripod threads

— OPTIONAL —

- 962B / 962GB With soft bag, target & Beamfinder™ Glasses
- 962S / 962GS With pouch & tripod (Kapro 886-19)

— KIT INCLUDES —

- 4 X AA batteries
- Multi-purpose magnetic mount
- Laser target
- Carrying case

873G/873 PROLASER® VECTOR



— QUALITY ASSURANCE —



— TECHNICAL DATA —

- Accuracy: ± 0.2 mm/m (± 0.0002 in/in)
- Self-leveling: $\pm 3^\circ$
- Self leveling type: Pendulum
- Green laser range:
 - Without detector: 30 m (100 ft)
 - With detector: 60 m (200 ft)
- Red laser range:
 - Without detector: 30 m (100 ft)
 - With detector: 50 m (165 ft)
- Shock resistant rubber over molded cover
- Adjustable metal folding legs for angle mounting and height adjustment
- Anti-slip grips
- Manual mode for angular layout / marking
- Pulse mode
- Visual & audible "Out of Leveling Range" warning
- 1/4" tripod thread

— OPTIONAL —



- 873S PROLASER® VECTOR SET with 3.2 m (10.5 ft) / 1.3 m (4.3 ft) pole tripod
- 873GS PROLASER® VECTOR SET red/ green laser, pole tripod (Kapro 886-58) and adjustable laser mount (1/4" thread)

— KIT INCLUDES —

- Soft carrying case
- 3 X AA batteries
- 5/8" tripod adaptor



872G/872 PROLASER® PLUS



— QUALITY ASSURANCE —



— TECHNICAL DATA —

- Accuracy: ± 0.2 mm/m (± 0.0002 in/in)
- Self-leveling: $\pm 3^\circ$
- Self leveling type: Pendulum
- Green laser range:
 - Without detector: 30 m (100 ft)
 - With detector: 60 m (200 ft)
- Red laser range:
 - Without detector: 30 m (100 ft)
 - With detector: 50 m (165 ft)
- Shock resistant rubber over molded cover
- Adjustable metal folding legs for angle mounting and height adjustment
- Anti-slip grips
- Manual mode for angular layout / marking
- Pulse mode
- Visual & audible "Out of Leveling Range" warning
- 1/4" tripod thread

— OPTIONAL —

- 872L PROLASER® PLUS with wall mount
- 872S/ 872GS PROLASER® PLUS SET with 1.3 m (4.3 ft) tripod

— KIT INCLUDES —

- 3 X AA batteries
- 5/8" tripod adaptor
- Carrying case




870G/870

VHX PROLASER® VIP



LASER BEAM LAYOUT



QUALITY ASSURANCE

IP65
WATER & DUST
RESISTANT

2 YEAR
LIMITED
WARRANTY

TECHNICAL DATA

- Accuracy: ± 0.2 mm/m (± 0.0002 in/in)
- Self-leveling: $\pm 3^\circ$
- Self-leveling type: Pendulum
- Green laser range:
 - Without detector: 30 m (100 ft)
 - With detector: 60 m (200 ft)
- Red laser range:
 - Without detector: 30 m (100 ft)
 - With detector: 50 m (165 ft)
- Shock resistant rubber over molded cover
- Manual mode for angular layout / marking
- Pulse mode
- Visual & audible "Out of Leveling Range" warning
- 1/4" tripod thread
- 5/8" tripod thread for flat & 90° mounting thread


KIT INCLUDES

- 3 X AA batteries
- Laser target
- Wall mount
- 5/8" tripod adaptor
- Carrying case



862G/862

PROLASER® CROSS LINE



QUALITY ASSURANCE

- IP54**
WATER & DUST
RESISTANT
- 2 YEAR**
LIMITED
WARRANTY

TECHNICAL DATA

- Laser accuracy:
 - Green laser: ± 0.4 mm/m (± 0.0004 in/in)
 - Red laser: ± 0.2 mm/m (± 0.0002 in/in)
- Self-leveling: $\pm 3^\circ$
- Self-leveling type: Pendulum
- Laser range without detector: 20 m (65 ft)
- Magnetic V-Groove back for easy mounting
- Hanging hole
- Manual mode for angular layout / marking
- Visual "Out of Leveling Range" warning
- Locking pendulum mechanism
- 1/4" tripod thread

OPTIONAL

- 862S/ 862GS PROLASER® CROSS LINE LASER SET with 1.3 m (4.3 ft) tripod


KIT INCLUDES

- Hook and loop strap
- 2 X AA batteries
- Soft carrying case



852G/852

PROLASER® CROSS LINE LASER



QUALITY ASSURANCE

- IP54**
WATER & DUST
RESISTANT
- 2 YEAR**
LIMITED
WARRANTY

TECHNICAL DATA

- Accuracy: ± 0.3 mm/m (± 0.0003 in/in)
- Self-leveling: $\pm 3^\circ$
- Self-leveling type: Pendulum
- Laser range:
 - Without detector: 15 m (50 ft)
 - With detector: 40 m (130 ft)
- Shock resistant rubber over molded cover
- Manual mode for angular layout / marking
- Pulse mode
- Visual "Out of Leveling Range" warning
- 1/4" tripod thread


KIT INCLUDES

- 3 X AA batteries



842G/842

PROLASER® BAMBINO™



QUALITY ASSURANCE

IP54
WATER & DUST
RESISTANT

2 YEAR
LIMITED
WARRANTY

TECHNICAL DATA

- Accuracy: ± 0.4 mm/m (± 0.0004 in/in)
- Self-leveling: $\pm 3^\circ$
- Self leveling type: Pendulum
- Laser range without detector: 15 m (50 ft)
- Shock resistant rubber over molded cover
- Manual mode for angular layout / marking
- Visual "Out of Leveling Range" warning
- 1/4" tripod thread

OPTIONAL

- Flexible Mini Tripod (886-08)


KIT INCLUDES

- 2 X AA batteries



896G

PROLASER® 5-DOT



QUALITY ASSURANCE

IP54
WATER & DUST
RESISTANT


2 YEAR
LIMITED
WARRANTY

TECHNICAL DATA

- Accuracy: ± 0.3 mm/m (± 0.0003 in/in)
- Self-leveling: $\pm 3.5^\circ$
- Self leveling type: Pendulum
- Laser range:
 - Without detector: 20 m (65 ft)
 - With detector: 50 m (165 ft)
- Shock resistant rubber over molded cover
- Hanging hole
- 1/4" and 5/8" tripod threads

KIT INCLUDES

- Magnetic multi-functional base
- Laser target
- 2 X AA batteries
- Hook and loop strap
- Soft carrying case



810 PROLASER® NAIL GRIPPER™



814 LINE LASER & STUD FINDER



893 T-LASER™



TECHNICAL DATA

- Laser range: up to 6 m (20 ft)
- 2 cylindrical vials:
 - 1 horizontal beam
 - 1 vertical beam
- Patented rubber grip for holding any size of nails or screws
- Pressure-activated power switch

KIT INCLUDES

- 2 X AAA batteries
- Magnetic wristband for holding nails or screws

TECHNICAL DATA

- Laser range: up to 6 m (20 ft)
- 2 cylindrical vials:
 - 1 vertical
 - 1 horizontal
- Integrated magnetic stud finder
- Angle-setting mount enables horizontal, vertical or 45° laser line
- Rubber overmold for improved grip

TECHNICAL DATA

- 90° highly visible laser beam
- Laser range: 3 m (10 ft)
- Spring grip slides onto edge of standard boards 6.4 mm - 15.9 mm (1/4" - 5/8")
- Pressure-activated power switch
- Bi-material molded case with rubber overlay
- Compact & ergonomic design
- Handy belt clip

KIT INCLUDES

- 2 X AAA batteries

830 AUTOMATIC OPTICAL LEVEL

QUALITY ASSURANCE



TECHNICAL DATA

- Accuracy 1.6 mm / 30 m
- x32 telescopic zoom
- Working range of up to 120 m (394 ft)
- 360° adjustable rotation
- Built-in lock to protect mechanism
- Zoom adjustment knob
- Angle estimation disc ruler
- Bull's eye surface level
- 5/8" tripod thread

KIT INCLUDES

- Carrying case
- Allen key
- Tuning pin
- Conical hook



816 & 509 SET



- 816 LINE LASER
- 509 MEASURING TAPE



842 & 510 SET



- 842 CROSS LINE LASER LEVEL
- 510 MEASURING TAPE



PRO ALL-IN-ONE KIT

KIT INCLUDES

- 842G Green Cross laser
- 771M-15CM Level with magnified vial and Milled, Magnetic V-Groove Base
- 309-30 cm Square with unique support ledge and angle marking
- 509-5M Measuring Tape
- 18 mm Rebound Cutting Knife
- Magnetic Flathead and Phillips Screwdrivers
- Flexible Mini Tripod
- 2x AA Batteries
- Ball Pen



377 KAPROMETER™ K7



QUALITY ASSURANCE



TECHNICAL DATA

- Measurements range: 0.05 - 100 m (0.16 - 328 ft)
- Accuracy: ±1.5 mm
- Resolution: 0.001 m
- Measurement speed: 0.5 Sec
- Battery life: 10,000 measurements
- Built-In flip cover
- Dynamic measuring
- Area / Volume / Pythagoras measurement
- Storage of up to 50 measurements
- Integrated inclinometer
- Up to 3 reference points
- 1/4" tripod thread

KIT INCLUDES

- 2 X AAA batteries
- Carrying pouch

QUALITY ASSURANCE



TECHNICAL DATA

- Measurements range: 0.05 - 30 m (0.16 - 100 ft)
- Accuracy: ±2 mm
- Resolution: 1 mm
- Measurement speed: 0.5 sec
- Battery life: 5000 measurements
- Built-In flip cover
- Keypad protection
- Area / Volume / Pythagoras measurement
- Dynamic measuring
- Storage of up to 20 measurements
- Up to 2 reference points

KIT INCLUDES

- 2 X AAA batteries
- Carrying pouch



363 KAPROMETER™ K3



379 MOISTURE METER



QUALITY ASSURANCE



TECHNICAL DATA

- Measurement range:
 - Timber moisture: 6% to 60%
 - Building material moisture: 1.5% to 33%
- Accuracy:
 - Moisture: ± 2%
 - Temperature: ± 2°C (± 4F)
- 8 calibration scales for various wood types
- Hold function for measurement freeze
- Ergonomic rubber overmold for improved gripping

KIT INCLUDES

- 2 X AAA batteries

QUALITY ASSURANCE



TECHNICAL DATA

- Detection depth:
 - Metal pipes: up to 18 mm (0.7")
 - Copper pipes: up to 30 mm (1.20")
 - Other metal objects: up to 50 mm (2")
 - Studs: up to 18 mm (0.7")
- Detection of AC wires, metal, wood and studs
- Detection buzzer
- Automatic scan

389 MULTISCANNER STUD FINDER



398 TERMOSCAN™



QUALITY ASSURANCE



TECHNICAL DATA

- Temperature measurement range: -50°C to 650°C (-58°F to 1202°F)
- Emissivity: 0.10 ~ 1.0 adjustable
- Optical resolution: 12:1 distance to spot size ratio
- Dual laser for accurate measurement
- Internal memory of up to 20 readings
- Adjustable high/low set points with audible alarm alerts
- Lock function for continuous reading

KIT INCLUDES

- Pouch
- 9V battery

397 DEEP VISION™ BORESCOPE



QUALITY ASSURANCE

IP67
WATER & DUST
RESISTANT

TECHNICAL DATA

- Temperature measurement range: 0°C to -40°C (32°F to -113°F)
- 8.5 mm high sensitivity camera
- Screen resolution: 320 x 240 px
- 3.5" true color LCD screen
- 4 GB internal memory
- 360° LCD image rotation
- Independent 1W light on front
- x 4 Zoom
- 1 m / 3 m (3 ft / 10 ft) flexible camera cable

KIT INCLUDES

- Carrying case
- USB charging cable
- 1 m / 3 m (3 ft / 10 ft) flexible camera cable

399 THERMO-VISION™



QUALITY ASSURANCE

IP54
WATER & DUST
RESISTANT

2 YEAR
LIMITED
WARRANTY

TECHNICAL DATA

- Measurement accuracy:
 - Up to 300°C: ±2°C or ±2%
 - Above 300°C: ±5%
- Temperature measurement range: 20°C to 450°C (-4° F to 842° F)
- Thermal image resolution: 160 x 120 px
- Visible image resolution: 0.3 Mp
- Thermal sensitivity: 0.07°C
- Provide a thermal image based on real-time temperature distribution
- 5 color pallets for optimal image clarity
- Switchable highest & lowest temperature cursors
- Built-in chargeable battery

KIT INCLUDES

- USB cable for charging and data transfer
- Carrying case



840G/840 BEAMFINDER™ GLASSES

- Enhances visibility of laser beam



845G/845 MAGNETIC LASER LEVEL TARGET

- For maximum visibility of laser beams projected onto non-solid surfaces
- Special reflective surface
- Graduations marks: cm | in
- Compact & lightweight design



894-04G/894-04 BEAM LASER DETECTOR

- Locate laser beams with laser levels of a corresponding color on pulse mode
- High accuracy: ± 1.5 mm
- Low accuracy: ± 2.5 mm
- Outdoor range: up to 50 m (165 ft)



886-23 UNIVERSAL MAGNETIC WALL MOUNT

- Clamping unit for mounting on profiles or pipes
- 1/4" thread (base thread is 1/8" & 1/4")
- Rare-Earth magnets
- Anti-slip padding
- 2 hanging holes



886-08 FLEXIBLE MINI TRIPOD

- Adjustable legs
- Height: 21 cm (8.26")



886-24 MULTIFUNCTIONAL MAGNETIC MOUNT

- 1/4" thread (base thread is 1/8" & 1/4")
- Rare-Earth magnets
- Anti-slip padding
- 2 hanging holes
- V-Groove
- Hook and loop strap
- Additional height adjustment



886-25 MAGNETIC MULTI- FUNCTIONAL BRACKET

- Locking screw for stability
- Standard 5/8" UNC thread
- 1/4" thread adaptor



886-19
LIGHTWEIGHT
ADJUSTABLE
LASER TRIPOD

- Adjustable legs up to: 1.50 m (4.92 ft)
- With carrying handle
- 1/4" thread



886-48
PROFESSIONAL
TRIPOD FOR
LASER LEVEL

- Adjustable legs up to: 2.32 m (7.61 ft)
- With scale and vial
- 5/8" thread



886-28
TRIPOD FOR
LASER LEVEL

- Adjustable legs up to: 1.5 m (4.92 ft)
- Strong lightweight tripod
- Alignment vial
- 5/8" thread



886-20
LASER ANGLE MOUNT

- Accurate indication of indicated angle



841
TRIPOD ADAPTER

- Convert tripod thread from 1/4" UNC to 5/8" UNC



886-30
EXTENDABLE POLE FOR
LASER LEVEL

- Self-clamping between floor to ceiling
- Maximum height: 3.2 m (10.5 ft)
- Adjustable laser mount with 5/8" UNC thread



886-58
POLE WITH TRIPOD

- Telescoping pole with locking sections
- Maximum height: 3.2 m (10.5 ft)
- Strong lightweight tripod stand with surface level
- Adjustable laser mount with 1/4" UNC thread





ZZCLASER24 / 02.2024

